




Technical Specifications


- 60 mm profile width,
- Large chamber and 2 seals, provides an excellent heat, sound and water insulation.
- Unique support sheet and automatic TPV gray seals all yield lower inventory cost and speedy manufacturing.
- Single layer (4-6 mm) or heat insulating glass (20-24-32 mm) at different thickness may be applied with gray seals.
- Furthermore, 3 layered glasses and blind glasses, with shutter (equipped with motor or motorless) or without shutter.









PRP.6100




Frame Profile With Border PRP.6700




Sash Profile PRP.6200




PRP.6300




Super Sash Profile PRP.7540




Door Sash Profile 85 mm PRP.6400




Door Sash Profile 92 mm PRP.6420




Mullion Rebate Profile PRP.6600




Door Sash Profile 100 mm PRP.6440



Outward Sash Profile PRP.6220




Outward Door Sash Profile PRP.6500




Outward Mullion Profile PRP.6320






90° Corner Connection Profile PRP.6910



Pipe Profile PRP. 6920



Angled Corner Connection Profile PRP. 6900




Frame/ Sash / Mullion Reinforcement



Mullion Reinforcement




Frame With Border Reinforcement



Door Sash 85 mm Reinforcement



Reinforcement





Door Sash 100 mm Reinforcement

53

Door Sash 100 mm Box

Reinforcement





90° Corner Connection Reinforcement


4

32

Mullion Rebate Reinforcement

40





4-6 mm Glazing Bead PRP.6800




20 mm Glazing Bead PRP.6802




24 mm Glazing Bead PRP.6804




32 mm Glazing Bead PRP.6806




4-6 mm Glass




20 mm Glass




24 mm Glass




32 mm Glass




4-6 mm Glass



20 mm Glass



24 mm Glass



32 mm Glass



